

Product Datasheet

--PTX Series



Product name: Stainless Steel Enclosures

Product description: PTX series 316L stainless steel enclosure is wall mounting type, used to protect the electrical parts assembled inside with simple, flexible interior installation.

Add: No 2, yongyi west road, fantan industrial zone, dipu, anji, huzhou, zhejiang, china

Post code: 313300

Tel: 0086-572-5093996 Fax: 0086-572-5093994 Cell-phone: 0086-18057255902

E-mail: dakotina@prota.cn

Website: www.prota.cn



ANJI HUACHENG ELECTRICS CO., LTD.

Product purpose: Applied for controlling and power distribution safety performance in low voltage area, it's waterproof and dustproof. We secure cable routing to a high standard protection.

Product structure: PTX series 316L stainless steel enclosure is mainly made of 316L, thickness: door & body: 1.2mm, mounting plate: 1.5mm for the height less than 800mm, door & body: 1.5mm, mounting plate: 2mm for over 800mm high.

Door & body are 316L, the inside mounting plate is galvanized steel.

Protection: PU foaming polyurethane gasket inside door, supplied good sealing performance on the boxes, which offers better performance on IP66 rating.

304AISI locking system with waterproof cap is also alternative, which offers better performance on IP66 rating.

There're also coming with the reversible hinged door--130 ° opening, foaming polyurethane gasket inside door, 2XM6 earth studs.

No plexiglass door, no inner door, no earthing wire, no door stop, no wall mounting brackets for the standard PTX series.

Surface treatment: To 316L stainless steel materials for door & body, hairline finish, grit blasting for the interior.

Operating temperature: -20°C~+50°C

Product approvals: RoHS, CE, IP66, IK10

Production Line: ISO9001

Add: No 2, yongyi west road, fantan industrial zone, dipu, anji, huzhou, zhejiang, china
Post code: 313300
Tel: 0086-572-5093996 Fax: 0086-572-5093994 Cell-phone: 0086-18057255902
E-mail: dakotina@prota.cn
Website: www.prota.cn